



WELLCOAT ACRYLIC PRIMER SEALER (white)

A copolymer acrylic base primer cum sealer containing alkali resisting pigments/extenders & low particle size emulsion for better penetration on to the surface thus most effectively sealing the surface & improving adhesion of the subsequent quotes. The product is compatible with similar products of any origin.

PRODUCT

Good penetration on to the wall. Compatible with all standard emulsion paints. Better opacity. Suitable for exterior application.

FEATURES

- **Area of Use :** Exterior & Interior
- **Substrate :** Concrete, plaster, masonry, brickwork blockwork, gypsum

RECOMMENDED USE

Applicable by Brush , Roller, Conventional spray. Airless spray is not suggested. Ensure adequate ventilation during application and drying. Stirr thoroughly before application. Apply two coats for optimal opacity. Use 5% to 10% thinner for ease of application depending on the method of application.

APPLICATION METHOD

- Finish** : Smooth, matt
- Colour** : White
- NVM %** : 20 ± 2
- Specific Gravity** : 1.24 ± 0.02
- Thinner/Cleaner** : Sweet Water / WT -AQ
- Pack size** : 1USG,5USG
- Theoretical coverage** : 6.5 m²/lt at 30 micron DFT
- Practical coverage** : While estimating the practical spread rates, due allowance should be made for surface profile, uneven application, over spray loss & losses in containers and equipment.

SPECIFICATION & OTHER INFORMATION

■ Drying Time

| Substrate temperature | Dry to touch | Overcoating interval | |
|-----------------------|--------------|----------------------|---------|
| | | Minimum | Maximum |
| 35°C | 2 hours | 5 hours | |
| 45°C | 1 hours | 4 hours | |

WELLCOAT ACRYLIC PRIMER SEALER(white)

Concrete, Plaster, Masonry (New & Unpainted)

Ensure surface is clean, dry and free from all contaminants. Surface must be sound and free from laitence. Remove laitence by wire brush or sweep blast & wipe clean. Apply one coat of Wellcoat acrylic primer sealer. Allow to dry & apply required quantity of Stucco putty followed by top coat. For Prepainted surface, loose & flaky material have to be removed by wire brushing or scrapping followed by complete dusting down. Apply a coat of antifungal solution & allow it to dry. Apply a thin coat of stabilizing primer & allow to dry for application of Covercoat acrylic primer sealer & Putty if necessary.

SURFACE PREPARATION & SYSTEM

Storage & Disposal : Store under cool & dry condition with adequate ventilation.
Dispose in land fill as per guidance of statutory authority
Don't empty the cans in drains, sewers or other water courses.

STORAGE & HANDLING

Flash point : Not applicable
Shelf life : 12 months in closed condition.

- Avoid contact with the skin and eyes. Wear protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream.
- Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.
- In case of accidental splashes wash the eyes with water & skin with mild soap & water. Never use solvent for cleaning body.
- In case of inhalation & ingestion expose the person to fresh air & finally consult doctor as quickly as possible.
- For details on Safety & Handling refer to MSDS.

SAFETY PRECAUTIONS & FIRST AID

The Product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system , proper surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.

DISCLAIMER