

Wellcoat Paints

Painting Solution



Wellcoat Paints
Architectural Coatings
Product Data Sheet

WELLCOAT ALKALI RESISTANT PRIMER

An aqueous premium quality alkali resisting primer based on pure acrylic emulsion. The product has very good penetrating power & sealing capability. It provides a sound base for improved adhesion of subsequent emulsion paint coats under external & internal conditions.

PRODUCT

Very good penetration. Pure acrylic binder gives superior alkali resistance Works as primer cum sealer . Recommended for exterior application. Less smell.

FEATURES

- **Area of Use** Interior & Exterior
- **Substrate** Concrete, plaster, masonry, brickwork, blockwork.

RECOMMENDED USE

Applicable by Brush , Roller, Conventional spray. Airless spray is not suggested. Ensure adequate ventilation during application and drying. Stirr thoroughly before application. Apply two coats for optimal opacity. Use 5% to 10% thinner for ease of application depending on the method of application.

APPLICATION METHOD

Finish : Smooth, Matt
Colour : White
NVM % : 30 ± 2
Specific Gravity : 1.34 ± 0.02
Thinner/Cleaner : Sweet Water /WT-AQ
Pack size : 1USG, 5USG
Theoretical Coverage : 10.5m²/lt at 30 micron DFT

SPECIFICATION & OTHER INFORMATION

Practical coverage : While estimating the practical spread rates, due allowance should be made for surface profile, uneven application, over spray, losses in containers and equipment.

■ Drying Time

Substrate temperature	Dry to touch	Overcoating interval	
		Minimum	Maximum
35°C	3 hours	5 hours	
45°C	2 hours	4 hours	Indefinite

Wellcoat Paints

Painting Solution



Wellcoat Paints
Architectural Coatings
Product Data Sheet

WELLCOAT ALKALI RESISTANT PRIMER

Concrete, Plaster, Masonry (New & Unpainted)

Ensure surface is clean, dry and free from all contaminants. Surface must be sound and free from laitence. Remove laitence by wire brush or sweep blast & wipe clean. Apply one coat of Wellcoat A.R primer. Allow to dry & apply required quantity of Stucco putty followed by top coat. For Prepainted surface loose, flaky material have to be removed by wire brushing or scrapping followed by complete dusting down. Apply a coat of antifungal solution & allow it to dry. Apply a thin coat of stabilizing primer & allow to dry for application of Wellcoat A.R primer. & Putty if necessary. use stucco putty for interior. For exterior use exterior filler.

SURFACE PREPARATION & SYSTEM

Storage & Disposal : Store under cool & dry condition with adequate ventilation. Dispose in land fill as per guidance of statutory authority Don't empty the cans in drains, sewers or other water courses.

STORAGE & HANDLING

Flash point : Not applicable.
Shelf life : 12 months under sealed condition.

- Avoid contact with the skin and eyes. Wear protective clothing goggles, dust mask and gloves. Use a barrier cream.
- Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray. In case of accidental splashes wash the eyes with water & skin with mild soap & water. Never use solvent for cleaning body. In case of inhalation & ingestion expose the person to fresh air & finally consult doctor as quickly as possible.
- For details on Safety & Handling refer to MSDS.

SAFETY PRECAUTIONS & FIRST AID

The Product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system , proper surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.

DISCLAIMER