

# Wellcoat Paints

Painting Solution



Wellcoat Paints  
Architectural Coatings  
Product Data Sheet

## WELLCOAT STUCCO PUTTY

A copolymer acrylic base filler containing alkali resisting & smooth sandable pigments & extenders, for the filling of surface irregularities and indentations, hairline surface cracks etc. It helps to produce a smooth and level surface prior to painting.

### PRODUCT

Very easily sandable to smooth surface. Good filling property & opacity. Flexible enough to be able to withstand surface expansion & contraction.

### FEATURES

- **Area of Use :** Interior Only
- **Substrate :** Concrete, plaster, masonry, gypsum, may also be used on timber

### RECOMMENDED USE

Use Putty applicator or Broad blade knife for application. Product can be applied on supply consistency but can be thinned by 5-10% with water for ease of application. Application under proper ventilation & moderate humidity gives best result.

### APPLICATION METHOD

- Finish** : Smooth
- Colour** : White, Off white, Light grey befitting top coat shade
- NVM %** : 50 ± 2
- Specific Gravity** : 1.79 ± 0.02
- Thinner/Cleaner** : Sweet Water / WT-AQ
- Pack size** : 1USG, 5USG
- Coverage** : Will depend on the quality of the surface & extent of filling required. However, 3-3.5 m<sup>2</sup> per kg per coat may be considered for reasonably smooth plastered surface.

### SPECIFICATION & OTHER INFORMATION

#### ■ Drying Time

Substrate temperature	Dry to touch	Overcoating interval	
		Minimum	Maximum
35°C	1 & 1/2 hours	5 hours	10 hours
45°C	1 hours	4 hours	8 hours

# Wellcoat Paints

Painting Solution



Wellcoat Paints  
Architectural Coatings  
Product Data Sheet

## WELLCOAT STUCCO PUTTY

### Concrete, Plaster, Masonry ( New & Unpainted )

Ensure surface is clean, dry and free from all contaminants. Surface must be sound and free from laitence. Remove laitence by wire brush or sweep blast & wipe clean. Apply one coat of Primer Sealer. Allow to dry & apply required quantity of Stucco putty followed by top coats. Don't use this putty for exterior purpose.

For Prepainted surface loose, flaky material have to be removed by wire brushing or scrapping followed by complete dusting down. Apply a coat of antifungal solution & allow it to dry. Apply a thin coat of stabilizing primer & allow to dry for application of Primer sealer & Putty if necessary.

### For Timber

Ensure surface is clean, dry and free from all contaminants.

Apply one coat of Synthetic Wood Primer. Allow to dry & apply a coat of stucco putty, if required. Don't apply Syntehtic wood primer if surface is wet or have large cavities.

### SURFACE PREPARATION & SYSTEM

**Storage & Disposal** : Store under cool, dry condition with proper ventilation. Disposal to be done as normal water based paint in land fill as per guidance of statutory authority . Don't empty the cans into drains, sewers or other water courses.

**Flash Point** : Not applicable

**Shelf Life** : Upto 12 months in closed condition

### STORAGE & HANDLING

- Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream.
- Ensure that there is adequate ventilation in the area where the product is being applied.
- For details on Safety & Handling pl refer to MSDS.

### SAFETY PRECAUTIONS & FIRST AID

The Product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system, proper surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.

### DISCLAIMER