

Wellcoat Paints

Painting Solution



Wellcoat Paints
Architectural Coatings
Product Data Sheet

POLYSHIELD ACRYLIC SPRAY COMPOUND

A copolymer acrylic based high build intermediate spray coat for Polyshield Tile Tex hybrid system. The product is convertible to various texture form & is supposed to be overcoated with Supercryl or Superthane top coat to form Polyshield hybrid Tile Tex system. The system possess outstanding durability with anticarbonation property.

PRODUCT

- Highly durable system with excellent chemical & mechanical resistance
- Very good dirt pick up resistance
- Available in several shades.

FEATURES

Intermediate coat for Polyshield hybrid Tile Tex system. Suggested for exterior & interior use over concrete, plaster, brick work & block work.

RECOMMENDED USE

The product is applied by a special hopper spray gun with higher orifice diameter (6-8mm) at 70-80 psi. Ensure adequate ventilation during spray & drying of the film & humidity during application doesn't exceed 95%

APPLICATION METHOD

Color	: White/Off-white & select shades
Finish	: Matt
NVM%	: 58-60
Thinner/Cleaner	: Sweet water/WT-AQ
Thinning volume	: 5-7% max
Typical DFT	: 250-400 microns
Theoretical coverage	: 1.5 to 2.5 m ² /lt
Practical coverage	: Would depend on surface quality, application skill, loss due to handling etc.
Drying time @ 300C	: Touch dry – 8 hrs
Recoating time	: 15-16 hrs
Pack size	: 1USG,5USG

SPECIFICATION & OTHER INFORMATION

After ensuring that surface is absolutely clean, dry & free of organic contaminants apply Polyshield hybrid Tile Tex system :
Wellcoat Tex primer (1 coat) + Polyshield acrylic spray compound (1 coat) + Wellcoat Supercryl (2 coats) Or
b) Wellcoat Tex primer (1 coat) + Polyshield acrylic spray compound (1 coat) + Wellcoat Superthane (2 coats)

SURFACE PREPARATION & SYSTEM

Wellcoat Paints

Painting Solution



Wellcoat Paints
Architectural Coatings
Product Data Sheet

POLYSHIELD ACRYLIC SPRAY COMPOUND

Storage & Disposal	: Store under cool & dry condition with adequate ventilation. Dispose in land fill as per guidance of statutory authority Don't empty the cans in drains, sewers or other water courses.
Flash point	: Not applicable
Shelf life	: 12 months in closed condition

STORAGE & HANDLING

- Avoid contact with the skin and eyes. Wear protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream.
- Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.
- In case of accidental splashes wash the eyes with water & skin with mild soap & water. Never use solvent for cleaning body.
In case of inhalation & ingestion expose the person to fresh air & finally consult doctor as quickly as possible.
- For details on Safety & Handling refer to MSDS.

SAFETY PRECAUTIONS & FIRST AID

The Product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system, proper surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.

DISCLAIMER