



**ACRYLIC PRIMER**

<p>Acrylic co-polymer-based primer containing alkali resisting pigments / extenders &amp; low particle size emulsion for better penetration on to the surface thus most effectively sealing the surface &amp; improving adhesion of the subsequent coats. The product is compatible with similar products of any origin.</p>	<p><b>PRODUCT</b></p>
<ul style="list-style-type: none"> <li>• Good penetration on to the wall.</li> <li>• Good opacity.</li> <li>• Compatible with all standard emulsion paints</li> <li>• Suitable for exterior application</li> </ul>	<p><b>FEATURES</b></p>
<p><b>Area of Use</b> : Exterior &amp; Interior <b>Substrate</b> : Concrete, plaster, masonry, brickwork blockwork, gypsum</p>	<p><b>RECOMMENDED USE</b></p>
<p>Finish : Smooth / Matt Colour : White NVM % : 35 ± 2 Specific Gravity : 1.52 ± 0.02 Thinner/Cleaner : Water Application Method : Brush, Roller and Spray Recommended DFT : 30 microns Recommended WFT : 130- 150 microns Theoretical Coverage : 10-12 m<sup>2</sup> /Ltr at 30 microns DFT Drying Time : 2 -3 Hours @ 30°C Pack size : 1USG,5USG</p>	<p><b>SPECIFICATION &amp; OTHER INFORMATION</b></p>

<p>Applicable by Brush , Roller, Conventional spray and Airless spray. Ensure adequate ventilation during application and drying. Stir thoroughly before application. Apply two coats for optimal opacity. Use 20 -30% thinner for ease of application depending on the method of application.</p>	<p><b>APPLICATION METHOD</b></p>
<p><b>Concrete, Plaster, Masonry ( New &amp; Unpainted )</b>          Ensure surface is clean, dry, and free from all contaminants. Surface must be sound and free from laitence. Remove laitence by wire brush or sweep blast &amp; wipe clean. Apply one coat of Wellcoat Acrylic Primer. Allow to dry &amp; apply required quantity of Stucco putty followed by top coat.</p> <p><b>For Prepainted surface</b>, loose &amp; flaky material must be removed by wire brushing or scrapping followed by complete dusting down. Apply a coat of antifungal solution &amp; allow it to dry. Apply a thin coat of stabilizing primer &amp; allow to dry for application of Wellcoat Acrylic Primer &amp; Stucco Putty if necessary followed by top coat.</p>	<p><b>SURFACE PREPARATION &amp; SYSTEM</b></p>
<p><b>Storage &amp; Disposal</b> : Store under cool &amp; dry condition with adequate ventilation.          Dispose in land fill as per guidance of statutory authority          Do not empty the cans in drains, sewers, or other water courses.</p> <p><b>Flash point</b> : Not applicable</p> <p><b>Shelf life</b> : 12 months in closed condition</p>	<p><b>STORAGE &amp; HANDLING</b></p>
<ul style="list-style-type: none"> <li>• Avoid contact with the skin and eyes. Wear protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream.</li> <li>• Ensure that there is adequate ventilation in the area where the product is being applied.</li> <li>• For details on Safety &amp; Handling refer to MSDS.</li> </ul>	<p><b>SAFETY PRECAUTIONS &amp; FIRST AID</b></p>
<p>The Product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of ,paint &amp; painting system, proper surface, surface preparation &amp; application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product. Product information sheet would be subject to modification as &amp; when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	<p><b>DISCLAIMER</b></p>