

2K GLOSS CLEAR

<p>2K Clear Coat is a high performance two component clearcoat formulated with superior quality Acrylic and Aliphatic isocyanate, that gives extreme gloss, fast drying, good adhesion, hardness, excellent chemical and weather resistance.</p>	<p>PRODUCT</p>																				
<ul style="list-style-type: none"> • Excellent gloss • Excellent adhesion and hardness • Scratch resistance • Chemical and weather resistance 	<p>FEATURES</p>																				
<p>Car repair, Industrial coating</p>	<p>RECOMMENDED USE</p>																				
<table border="0"> <tr> <td>Finish</td> <td>:Smooth</td> </tr> <tr> <td>Viscosity</td> <td>: 120 ± 20 Sec (Ford Cup No:4 @30°C)</td> </tr> <tr> <td>Colour</td> <td>: Clear, Water White</td> </tr> <tr> <td>Density</td> <td>: 1 ± 0.1 gram / cm³</td> </tr> <tr> <td>Mixing ratio</td> <td>: Base :Hardener = 2:1 (Volume)</td> </tr> <tr> <td>Thinner</td> <td>: 2K Acrylic Thinner (20-30%)</td> </tr> <tr> <td>Method of Application</td> <td>: Conventional spray, Curtain coat, Automatic</td> </tr> <tr> <td>Practical coverage</td> <td>: would depend on the surface profile, application skill & method, loss in the container.</td> </tr> <tr> <td>Drying time @ 30°C</td> <td>: Dust Free 30 minutes, Tack free: 3-4 Hours Hard dry over night</td> </tr> <tr> <td>Pack size</td> <td>: 1 LTR</td> </tr> </table>	Finish	:Smooth	Viscosity	: 120 ± 20 Sec (Ford Cup No:4 @30°C)	Colour	: Clear, Water White	Density	: 1 ± 0.1 gram / cm ³	Mixing ratio	: Base :Hardener = 2:1 (Volume)	Thinner	: 2K Acrylic Thinner (20-30%)	Method of Application	: Conventional spray, Curtain coat, Automatic	Practical coverage	: would depend on the surface profile, application skill & method, loss in the container.	Drying time @ 30°C	: Dust Free 30 minutes, Tack free: 3-4 Hours Hard dry over night	Pack size	: 1 LTR	<p>SPECIFICATION & OTHER INFORMATION</p>
Finish	:Smooth																				
Viscosity	: 120 ± 20 Sec (Ford Cup No:4 @30°C)																				
Colour	: Clear, Water White																				
Density	: 1 ± 0.1 gram / cm ³																				
Mixing ratio	: Base :Hardener = 2:1 (Volume)																				
Thinner	: 2K Acrylic Thinner (20-30%)																				
Method of Application	: Conventional spray, Curtain coat, Automatic																				
Practical coverage	: would depend on the surface profile, application skill & method, loss in the container.																				
Drying time @ 30°C	: Dust Free 30 minutes, Tack free: 3-4 Hours Hard dry over night																				
Pack size	: 1 LTR																				

<p>Conventional & Automatic spray e.g. Shefla applicators are most recommended method but can be applied by brush & roller over a small area.</p> <p>Ensure the surface is dry, clean, free from grease & other organic contaminants, well sanded & dusted. Soak the surface with PU thinner with the help of sponge or rags for 10 minutes.</p> <p>(This is a two-part product. Mix Base Hardener & Thinner (if required) as per ratio mentioned in the can. Mix thoroughly & wait for seven minutes before application for effervescence to subside). Ensure adequate ventilation during mixing, application and drying. Do not apply coating when surface temperature is 3°C or more above dew point.</p> <p>May require additional 5-7% thinner depending on ambient temperature & method of application.</p>	<p>SURFACE PREPARATION & APPLICATION</p>
<p>Storage & Disposal : Store in cool, dry condition. & dispose by controlled land fill as per requirement of statutory authority. Don't empty into drains, sewers or other water courses.</p> <p>Avoid part use from the Hardener pack & never keep the lid of hardener pack open.</p> <p>Avoid part use of the Hardener. It is filled in stoichiometric quantity</p> <p>Flash Point : 22°C</p> <p>Shelf Life : Upto 12 months under sealed condition.</p>	<p>STORAGE & HANDLING</p>
<ul style="list-style-type: none"> ▪ Avoid contact with the skin and eyes. Wear suitable protective clothings such as overalls, goggles, dust mask and gloves. Use a barrier cream. ▪ Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray. ▪ This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge. In case of fire, blanket flames with foam, carbon-dioxide or dry chemicals. ▪ Eyes & Skin: In the event of accidental splashes, flush eyes with warm water & wash skin with mild soap and seek quick medical advice. Never use solvent for cleaning the affected areas. ▪ Inhalation & Ingestion: Remove to fresh air, loosen collar. Don't induce vomiting. 	<p>SAFETY PRECAUTIONS & FIRST AID</p>
<p>The product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system, proper surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product.</p> <p>Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	<p>DISCLAIMER</p>