



Weathershield Matt Emulsion

<p>A premium quality water-based paint based on 100% pure acrylic emulsion pigmented with rutile titanium dioxide and light / alkali resistant pigments and extenders. The product has excellent scrub resistance and wash ability and having high crack bridge ability up to 0.1 to 1 mm. The biocides content in the product is adequate to resist fungus and algae growth under interior or exterior application condition thus making it suitable for both purposes.</p>	<p>PRODUCT</p>
<ul style="list-style-type: none"> • Smooth Matt Finish. • Anti-Carbonation property • Low Odor • Available in several shades. 	<p>FEATURES</p>
<p>Area of Use : Interior and Exterior Substrate : Ideal for concrete, plaster, brick work & block work.</p>	<p>RECOMMENDED USE</p>
<p>Color : As per company standard shade card Finish : Matt NVM% : 38 ± 2 Specific Gravity : 1.35± 0.02 Thinner/Cleaner :Water Thinning volume : 10- 30% max Application Method : Roller, Brush, Spray (Conventional and airless) Typical DFT : 30-40 microns Theoretical coverage : 10 - 13 m²/lt Practical coverage : Would depend on surface quality, application skill, loss due to handling etc. Drying time @ 30°C : Touch dry – 2 hour Recoating time : 2 hours Hard Dry : 4 hours Pack size : 1USG,5USG</p>	<p>SPECIFICATION & OTHER INFORMATION</p>

<p>For optimal performance substrates need to be properly prepared as outlined below</p> <p>Concrete, Plaster, Masonry</p> <p>New & unpainted surface</p> <p>Ensure surface is clean, dry, and free from all contaminants including Mould, Algae & Fungus by wire brushing followed by flushing with clean water.</p> <p>Interior</p> <p>Apply one coat of Wellcoat Alkali Resistant Primer, allow to dry. Apply enough Wellcoat Stucco Putty for obliteration of irregularities. Allow to dry. Smoothen the surface with sand paper & dust off. Apply two coats of Weathershield Matt Emulsion.</p> <p>Exterior</p> <p>Apply one coat of Wellcoat Alkali resistant primer or Wellcoat Acrylic primer and allow to dry. Do not use Filler in exterior application. Apply two coats of Weathershield Matt Emulsion</p>	<p>SURFACE PREPARATION & APPLICATION</p>
---	---

<p>Storage & Disposal : Store under cool & dry condition with adequate ventilation. Dispose in land fill as per guidance of statutory authority Don't empty the cans in drains, sewers or other water courses.</p> <p>Flash point : Not applicable</p> <p>Shelf life : 12 months in closed condition</p>	<p>STORAGE & HANDLING</p>
---	--

<ul style="list-style-type: none"> • Avoid contact with the skin and eyes. Wear protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. • Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray. • In case of accidental splashes wash the eyes with water & skin with mild soap & water. Never use solvent for cleaning body. • In case of inhalation & ingestion expose the person to fresh air & finally consult doctor as quickly as possible. ▪ For details on Safety & Handling refer to MSDS. 	<p>SAFETY PRECAUTIONS & FIRST AID</p>
--	--

<p>The Product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system, proper surface, surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	<p>DISCLAIMER</p>
---	--------------------------