



Wellcoat Weathershield Thermo

<p>Wellcoat Weathershield Thermo is flexible thermal insulation as well as a concrete protection coating based on acrylic emulsion. It is based on high quality binder which provides maximum protection to dry film. Its attractive texture hides the imperfections on the surface when applied with a sponge roller or trowel.</p>	<p>PRODUCT</p>
<ul style="list-style-type: none"> • Provides Thermal insulation & anti-carbonation properties • Exceptional outdoor durability • Excellent chemical, mechanical & abrasion resistance 	<p>FEATURES</p>
<p>Suggested for exterior use over concrete, plaster, gypsum, brick work & block work.</p>	<p>RECOMMENDED USE</p>
<p>Color : White/Off-white & select shades Finish : Texture NVM% : 50±2 Thinner/Cleaner : Sweet Water/WT-Aq Typical DFT : 150-1000 microns Theoretical coverage : 3-4 m²/lt Application Method : Roller, Brush or Spray Practical coverage : Would depend on surface quality, application skill, loss due to handling etc. Drying time @ 35°C : Touch dry – 60 minutes Recoating time : 6 hrs Minimum Maximum Indefinite Pack size : 1USG,5USG Application Condition : Apply this product only if Relative Humidity is less than 90% and substrate temperature is minimum 10°C & above 3°C the dew point. Moisture content should be 12-20%</p>	<p>SPECIFICATION & OTHER INFORMATION</p>

<p>After ensuring that surface is clean, dry & free of organic contaminants apply one coat of Wellcoat Acrylic Primer followed by a coat of Wellcoat Penetrating Primer or Wellcoat Tex Primer and allow it to dry. Do not use filler in case of exterior application. Smoothen the surface by sanding. Dust it off and apply one coat of Wellcoat Weathershield Thermo.</p>	<p>SURFACE PREPARATION & SYSTEM</p>
<p>Storage & Disposal : Store under cool & dry condition with adequate ventilation. Dispose in land fill as per guidance of statutory authority Do not empty the cans in drains, sewers, or other water courses.</p> <p>Flash point : Not Applicable</p> <p>Shelf life : 12 months in closed condition</p>	<p>STORAGE & HANDLING</p>
<ul style="list-style-type: none"> • Avoid contact with the skin and eyes. Wear protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. • Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapor or spray. • In case of accidental splashes wash the eyes with water & skin with mild soap & water. Never use solvent for cleaning body. • In case of inhalation & ingestion expose the person to fresh air & finally consult doctor as quickly as possible. <ul style="list-style-type: none"> ▪ For details on Safety & Handling refer to MSDS. 	<p>SAFETY PRECAUTIONS & FIRST AID</p>
<p>The Product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system, proper surface, surface preparation & application. Unless specifically agreed in writing by us we will not be responsible for 100% performance of the product. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	<p>DISCLAIMER</p>