



STUCCO PUTTY

<p>A copolymer acrylic base filler containing alkali resisting & smooth sandable pigments & extenders, for the filling of surface irregularities and indentations, hairline surface cracks etc. It helps to produce a smooth and level surface prior to painting</p>	<p>PRODUCT</p>																
<ul style="list-style-type: none"> • Good filling property. • Good opacity. • Very easily sandable to smooth surface. 	<p>FEATURES</p>																
<p>Concrete, plaster, masonry, gypsum, may also be used on timber</p>	<p>RECOMMENDED USE</p>																
<table border="0"> <tr> <td>Finish</td> <td>: Smooth</td> </tr> <tr> <td>Colour</td> <td>: White</td> </tr> <tr> <td>NVM %</td> <td>: 50 ± 2</td> </tr> <tr> <td>Specific Gravity</td> <td>: 1.79 ± 0.02</td> </tr> <tr> <td>Thinner/Cleaner</td> <td>: Sweet Water / WT-AQ</td> </tr> <tr> <td>Pack size</td> <td>: 1USG,5USG</td> </tr> <tr> <td>Coverage :</td> <td>Will depend on the quality of the surface & extent of filling required. However, 3-3.5 m² per kg per coat may be considered for reasonably smooth plastered surface.</td> </tr> <tr> <td>Drying Time</td> <td>: 1 hour 30 minutes @ 30°C</td> </tr> </table>	Finish	: Smooth	Colour	: White	NVM %	: 50 ± 2	Specific Gravity	: 1.79 ± 0.02	Thinner/Cleaner	: Sweet Water / WT-AQ	Pack size	: 1USG,5USG	Coverage :	Will depend on the quality of the surface & extent of filling required. However, 3-3.5 m ² per kg per coat may be considered for reasonably smooth plastered surface.	Drying Time	: 1 hour 30 minutes @ 30°C	<p>SPECIFICATION & OTHER INFORMATION</p>
Finish	: Smooth																
Colour	: White																
NVM %	: 50 ± 2																
Specific Gravity	: 1.79 ± 0.02																
Thinner/Cleaner	: Sweet Water / WT-AQ																
Pack size	: 1USG,5USG																
Coverage :	Will depend on the quality of the surface & extent of filling required. However, 3-3.5 m ² per kg per coat may be considered for reasonably smooth plastered surface.																
Drying Time	: 1 hour 30 minutes @ 30°C																
<p>Use Putty applicator or Broad blade knife for application. Product can be applied on supply consistency but can be thinned by 5-10% with water for ease of application. Application under proper ventilation & moderate humidity gives best result.</p>	<p>APPLICATION METHOD</p>																

<p>Concrete, Plaster, Masonry (New & Unpainted) Ensure surface is clean, dry and free from all contaminants. Surface must be sound and free from laitance. Remove laitance by wire brush or sweep blast & wipe clean. Apply one coat of Primer Sealer. Allow to dry & apply required quantity of Stucco putty followed by top coats. Don't use this putty for exterior purpose. For Pre-painted surface loose, flaky material have to be removed by wire brushing or scrapping followed by complete dusting down. Apply a coat of antifungal solution & allow it to dry. Apply a thin coat of stabilizing primer & allow to dry for application of Primer sealer & Putty if necessary.</p> <p>For Timber Ensure surface is clean, dry and free from all contaminants. Apply one coat of Synthetic Wood Primer. Allow to dry & apply a coat of stucco putty, if required. Do not apply Syntehtic wood primer if surface is wet or have large cavities.</p>	<p>SURFACE PREPARATION & SYSTEM</p>
---	--

<p>Storage & Disposal : Store under cool & dry condition with adequate ventilation. Dispose in land fill as per guidance of statutory authority Don't empty the cans in drains, sewers or other water courses.</p> <p>Flash point : Not applicable</p> <p>Shelf life : 12 months in closed condition</p>	<p>STORAGE & HANDLING</p>
---	--------------------------------------

<ul style="list-style-type: none"> • Avoid contact with the skin and eyes. Wear protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. • Ensure that there is adequate ventilation in the area where the product is being applied. • For details on Safety & Handling refer to MSDS. 	<p>SAFETY PRECAUTIONS & FIRST AID</p>
--	--

<p>The Product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of substrate ,paint & painting system, proper surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	<p>DISCLAIMER</p>
---	--------------------------