



PLASTIC EMULSION

<p>A dead matt emulsion paint based on Acrylic co-polymer pigmented with titanium dioxide and other light fast and alkali resisting pigments. It is ideal for residential, commercial, institutional surfaces. It is a non-washable emulsion. The product is most suitable for interior use.</p>	<p>PRODUCT</p>
<ul style="list-style-type: none"> • Good coverage • Faster drying. • Good application property. • Low VOC 	<p>FEATURES</p>
<p>Area of Use : Interior Substrate : Concrete, plaster, masonry, gypsum, brick.</p>	<p>RECOMMENDED USE</p>
<p>Finish : Smooth, matt Colour : As per company shade card. Special shades on request. NVM % : 40 ± 2% Specific Gravity : 1.52 ± 0.02 Drying : Touch dry – 30 minutes Thinner/Cleaner : Water Theoretical Coverage : 8- 10 m²/ Ltr at 30 microns DFT Practical Coverage : While estimating the practical coverage, due allowance should be made for surface profile, uneven application, over spray, losses in containers and equipment. Pack size : 1USG,5USG</p>	<p>SPECIFICATION & OTHER INFORMATION</p>

<p>Concrete, Plaster, Masonry (New & Unpainted) Ensure surface is clean, dry, and free from all contaminants. Surface must be sound and free from laitance. Remove laitance by wire brush or sweep blast & wipe clean. Apply one coat of Wellcoat PVA Primer. Allow to dry & apply required quantity of Stucco followed by 2 coats of Wellcoat Plastic Emulsion.</p> <p>For Prepainted surface, loose & flaky material must be removed by wire brushing or scrapping followed by complete dusting down Apply one coat of Wellcoat PVA Primer. Allow to dry & apply of Stucco Putty if required, followed by 2 coats of Wellcoat Plastic Emulsion.</p>	<p>SURFACE PREPARATION & APPLICATION</p>
--	---

<p>Storage & Disposal : Store under cool & dry condition with adequate ventilation. Dispose in land fill as per guidance of statutory authority Do not empty the cans in drains, sewers, or other water courses.</p> <p>Flash point : 25°C Shelf life : 12 months in closed condition</p>	<p>STORAGE & HANDLING</p>
---	--

<ul style="list-style-type: none"> • Avoid contact with the skin and eyes. Wear protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. • Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapor or spray. • In case of accidental splashes wash the eyes with water & skin with mild soap & water. Never use solvent for cleaning body. • In case of inhalation & ingestion expose the person to fresh air & finally consult doctor as quickly as possible. ▪ For details on Safety & Handling refer to MSDS. 	<p>SAFETY PRECAUTIONS & FIRST AID</p>
---	--

<p>The Product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system, proper surface preparation & application. Unless specifically agreed in writing by us we will not be responsible for 100% performance of the product. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	<p>DISCLAIMER</p>
--	--------------------------