



Supercoat Matt Emulsion(EXT)

<p>An economic grade water-based finish paint based on acrylic copolymer emulsion pigmented with rutile titanium dioxide and light / alkali resistant pigments and extenders. The product has excellent scrub resistance and wash ability and having high crack bridge ability up to 0.1 to 1 mm. The biocides content in the product is adequate to resist fungus and algae growth under interior or exterior application condition thus making it suitable for both purposes.</p>	<p>PRODUCT</p>
<ul style="list-style-type: none"> • Smooth Matt Finish. • Easy to apply • Low Odor • Available in several shades. 	<p>FEATURES</p>
<p>Area of Use : Interior and Exterior Substrate : Ideal for concrete, plaster, brick work & block work.</p>	<p>RECOMMENDED USE</p>
<p>Color : As per company standard shade card Finish : Matt NVM% : 40 ± 2 Specific Gravity : 1.42 ± 0.02 Thinner/Cleaner :Water Thinning volume : 10- 30% max Application Method : Roller, Brush, Spray (Conventional and airless) Typical DFT : 30-40 microns Theoretical coverage : 10 - 13 m²/lt Practical coverage : Would depend on surface quality, application skill, loss due to handling etc. Drying time @ 30°C : Touch dry – 2 hour Recoating time : 2 hours Hard Dry : 4 hours Pack size : 1USG,5USG</p>	<p>SPECIFICATION & OTHER INFORMATION</p>

<p>For optimal performance substrates need to be properly prepared as outlined below</p> <p>Concrete, Plaster, Masonry</p> <p>New & unpainted surface</p> <p>Ensure surface is clean, dry, and free from all contaminants including Mould, Algae & Fungus by wire brushing followed by flushing with clean water.</p> <p>Interior</p> <p>Apply one coat of Wellcoat Alkali Resistant Primer, allow to dry. Apply enough Wellcoat Stucco Putty for obliteration of irregularities. Allow to dry. Smoothen the surface with sand paper & dust off. Apply two coats of Supercoat Matt Emulsion (Exterior).</p> <p>Exterior</p> <p>Apply one coat of Wellcoat Alkali resistant primer or Wellcoat Acrylic primer and allow to dry. Do not use Filler in exterior application. Apply two coats of Supercoat Matt Emulsion (Exterior).</p>	<p>SURFACE PREPARATION & APPLICATION</p>
--	---

<p>Storage & Disposal : Store under cool & dry condition with adequate ventilation. Dispose in land fill as per guidance of statutory authority Don't empty the cans in drains, sewers or other water courses.</p> <p>Flash point : Not applicable</p> <p>Shelf life : 12 months in closed condition</p>	<p>STORAGE & HANDLING</p>
---	--

<ul style="list-style-type: none"> • Avoid contact with the skin and eyes. Wear protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. • Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray. • In case of accidental splashes wash the eyes with water & skin with mild soap & water. Never use solvent for cleaning body. • In case of inhalation & ingestion expose the person to fresh air & finally consult doctor as quickly as possible. ▪ For details on Safety & Handling refer to MSDS. 	<p>SAFETY PRECAUTIONS & FIRST AID</p>
--	--

<p>The Product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system, proper surface, surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	<p>DISCLAIMER</p>
---	--------------------------