



**Supercoat Silk Emulsion**

<p>A premium quality silk finish emulsion primarily intended for interior use. The product is based on acrylic co-polymer emulsion &amp; high percentage of Rutile &amp; other premium quality pigments. It has superb wet scrub resistance, resistance to fungus &amp; algae &amp; almost odor free. A beautiful velvet finish with wide variety of soothing shades coupled with resistance to scrub &amp; micro-organism growth make this product an ideal choice for interior of luxury homes &amp; high traffic areas requiring regular cleaning. The product is environment friendly &amp; easy to apply.</p>	<p><b>PRODUCT</b></p>
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------

<ul style="list-style-type: none"> <li>• Attractive semi reflective sheen</li> <li>• Contains UV resistant pigments which enhances lasting of topcoat.</li> <li>• Ideal for interior of luxury home</li> <li>• Available in several shades.</li> </ul>	<p><b>FEATURES</b></p>
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------

<p><b>Area of Use</b> <b>Substrate</b></p>	<p>: Interior ( can be used over partially exposed exterior also) : Ideal for concrete, plaster, brick work &amp; block work.</p>	<p><b>RECOMMENDED USE</b></p>
------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------	-------------------------------

<p><b>Color</b> <b>Finish</b> <b>NVM%</b> <b>Specific Gravity</b> <b>Thinner/Cleaner</b> <b>Thinner Volume</b> <b>Application Method</b> <b>Typical DFT</b> <b>Theoretical coverage</b> <b>Practical coverage</b>  <b>Drying time @ 30°C</b> <b>Recoating time</b> <b>Hard Dry</b> <b>Pack size</b></p>	<p>: As per company standard shade card : Smooth with velvet type silky finish : 40 ± 2 : 1.30 ± 0.02 :Water : 5-10% max : Roller, Brush, Spray (Conventional and airless) : 40 - 50 microns : 9 - 12 m<sup>2</sup>/lt : Would depend on surface quality, application skill, loss due to handling etc. : Touch dry – 1 hour : 2 hours : 12 hours : 1USG,5USG</p>	<p><b>SPECIFICATION &amp; OTHER INFORMATION</b></p>
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------

<p>For optimal performance substrates need to be properly prepared as outlined below</p> <p><b>Concrete, Plaster, Masonry</b>  <b>New &amp; unpainted surface</b></p> <p>Ensure surface is clean, dry, and free from all contaminants including Mould, Algae &amp; Fungus by wire brushing followed by flushing with clean water.</p> <p><b>Interior</b></p> <p>Apply one coat of Wellcoat Alkali Resistant Primer, allow to dry. Apply enough Wellcoat Stucco Putty for obliteration of irregularities. Allow to dry. Smoothen the surface with sand paper &amp; dust off. Apply two coats of Supercoat Silk Emulsion Or one coat of Supercoat Matt Emulsion followed by one or two coats of Supercoat Silk Emulsion.</p> <p><b>Exterior</b></p> <p>Apply one coat of Wellcoat Alkali resistant primer or Wellcoat Acrylic primer and allow to dry. Do not use Filler in exterior application. Apply two coats of Supercoat Silk Emulsion.</p>	<p><b>SURFACE PREPARATION &amp; APPLICATION</b></p>
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------

<p><b>Storage &amp; Disposal</b> : Store under cool &amp; dry condition with adequate ventilation.  Dispose in land fill as per guidance of statutory authority  Don't empty the cans in drains, sewers or other water courses.</p> <p><b>Flash point</b> : Not applicable</p> <p><b>Shelf life</b> : 12 months in closed condition</p>	<p><b>STORAGE &amp; HANDLING</b></p>
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------

<ul style="list-style-type: none"> <li>• Avoid contact with the skin and eyes. Wear protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream.</li> <li>• Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.</li> <li>• In case of accidental splashes wash the eyes with water &amp; skin with mild soap &amp; water. Never use solvent for cleaning body.</li> <li>• In case of inhalation &amp; ingestion expose the person to fresh air &amp; finally consult doctor as quickly as possible.</li> <li>▪ For details on Safety &amp; Handling refer to MSDS.</li> </ul>	<p><b>SAFETY PRECAUTIONS &amp; FIRST AID</b></p>
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------

<p>The Product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint &amp; painting system, proper surface preparation &amp; application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product.  Product information sheet would be subject to modification as &amp; when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	<p><b>DISCLAIMER</b></p>
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------