

# Wellcoat Paints

Painting Solution



Wellcoat Paints  
Wood Coatings  
Product Data Sheet

## MAXIWOOD SOLVO STAIN

A ready to use solvent based wood stain with deep penetration, quicker drying & low odor for coloration of hard/soft woods, particle boards, veneer & ply wood. The product is available in seven deep base shades & fifteen mixed shades which can be further mixed to achieve customized shades. The product is compatible with all solvent based wood coatings system e.g Nitrocellulose, Acid catalyzed system, 2 Pack polyurethane & single pack polyurethane.

### PRODUCT

Quick drying & deep penetration  
Low odor  
Simple application  
Scratch resistant

### FEATURES

Soluble dye ( Metal complex) & organic pigments  
Carrier vehicle & surface active agent  
Oxygenated solvent

### COMPOSITION

Maxiwood solvo stain is used as interior color coat on soft, hard woods, particle board for all application areas. The product should be top coated with a clear coat .

### RECOMMENDED USE

Brush, conventional spray, synthetic pad applicator, cotton rag soaked in stain are common application methods. For large surface 5% dilution with thinner WT-3 may be necessary. Ensure wood is clean free from grease & resin evenly sanded & dusted. For best result moisten wood with WT-3 & allow to dry. Stain should be thoroughly stirred before use for color consistency. Always test the stain before use on a small inconspicuous area of the wood to check shade & compatibility. Apply the stain evenly to the surface. After 2-3 minutes surplus stain should be spread & evened out using long brush strokes in the direction of grain ( very soft brush should be used). Allow the stain dry thoroughly then apply Maxiwood clear coat ( NC, AC or 2PPU) by spray.

### SURFACE PREPARATION & APPLICATION

# Wellcoat Paints

Painting Solution



Wellcoat Paints  
Wood Coatings  
Product Data Sheet

## MAXIWOOD SOLVO STAIN

Variants : Standard , Scratch resistant, Intense  
Viscosity : 20-22 sec B4/30°C  
Specific gravity : 0.98-1.02  
Gloss : Flat  
Adhesion : Excellent  
Shades : As per company supplied shade card  
Pack size : 1 LT, 5LT, 20LT  
Coverage : 10-15 sq mts/lit depending on surface condition & application method.  
Thinner/tool cleaner : WT-3

### SPECIFICATION & OTHER INFORMATION

Storage & Disposal : Store in cool, dry condition. & dispose by controlled land fill as per requirement of statutory authority. Don't empty into drains, sewers or other water courses.

### STORAGE & HANDLING

Flash Point : >40 C  
Shelf Life : Upto 12 months in closed condition.

- Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream.
- Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.
- In the event of accidental splashes, flush eyes with warm water & wash skin with mild soap and seek quick medical advice.  
Inhalation & Ingestion : Remove to fresh air, loosen collar. Don't induce vomiting. Refer to MSDS for details.

### SAFETY PRECAUTION & FIRST AID

The Product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system , proper surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.

### DISCLAIMER