

MAXIWOOD N.C PUTTY / FILLER

<p>Maxiwood NC putty is a quick drying easy to apply filler for wood as well as metal substrates. The product is available in semi-transparent form with excellent filling & sanding property for wood. It is used as wood grain filler & applied over bare wood before sanding sealer application. Another variety of NC putty available for metal substrate primarily used in the Automotive repair system.</p>	<p>PRODUCT</p>
<ul style="list-style-type: none"> • Very good filling property, • Cover imperfection of wood substrate • Semi-transparent hence maintain wood's natural look • Can develop adequate film build giving rise to excellent finish of the system. 	<p>FEATURES</p>
<p>Natural wood or wood substitutes like plywood, particle board, veneer. The product is most suitable for use with Nitrocellulose paints but can be used with AC lacquer & 2 Pack PU (interior) system.</p>	<p>RECOMMENDED USE</p>
<p>Specific gravity : 1.43-1.45 % NVM : Appx 70% Viscosity/ Consistency : 200,000 cPS @30°C & thixotropic Thinning : Not required Drying & Sanding time : 30 minutes at 30°C Method of application : Putty knife, Spatula, Stopping knife Pack size : 1LT.1 USG, 5 USG</p>	<p>SPECIFICATION & OTHER INFORMATION</p>

<p>Storage & Disposal Store in cool, dry condition keeping container tightly closed in accordance with petroleum (mixture) order, SRO 1929 No 993. & dispose by controlled land fill as per requirement of statutory authority. Don't empty into drains, sewers or other water courses.</p> <p>Flash Point : Below 20°C, Highly flammable.</p> <p>Shelf Life : Upto 12 months in closed condition</p>	<p>STORAGE & HANDLING</p>
---	--------------------------------------

<p>Ensure wood is dry, clean & free from contaminants. Sand the surface with a coarse Emery (180) along the direction of grains. Dust off the surface & apply a coat of Maxiwood N.C. Putty with putty knife, allow it to dry & sand the surface with Emery paper 180 followed by Emery paper no 320 for smooth finish before application of Sanding sealer & Topcoat. Maxiwood N.C. Putty is tintable with Maxiwood stain to achieve wood's actual color or any pastel tint. Not advised to match deep color using wood stain.</p> <p>Product's high solid formula ensures single coat application for desired result.</p>	<p>SURFACE PREPARATION & APPLICATION</p>
---	---

<ul style="list-style-type: none"> ▪ Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. ▪ Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapor or spray. ▪ This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge. In case of fire, blanket flames with foam, carbon-dioxide or dry chemicals. ▪ Eyes & Skin: In the event of accidental splashes, flush eyes with warm water & wash skin with mild soap and seek quick medical advice. Never use solvent for cleaning the affected areas. ▪ Inhalation & Ingestion: Remove to fresh air, loosen collar. Don't induce vomiting. 	<p>SAFETY PRECAUTIONS & FIRST AID</p>
--	--

<p>The product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system, proper surface, surface preparation & application. Wellcoat Paints warranty product quality only. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	<p>DISCLAIMER</p>
---	--------------------------