

**Maxiwood PU Varnish**

<p>Maxiwood PU varnish is a single pack polyurethane alkyd based clear coating designed for wooden surface. The product enhances the natural look of wood &amp; has good resistance to normal mechanical &amp; chemical attack including water &amp; moisture. It is also resistant to microorganism &amp; termite growth &amp; can withstand moderate temperature hence very useful for kitchen &amp; bathroom. The product works very well in wooden floor &amp; stairs with heavy wear. The product is available in clear &amp; variety of wood colors in high gloss, matt &amp; silk-matt version.</p>	<p><b>PRODUCT</b></p>
<ul style="list-style-type: none"> <li>• Fully dried film is resistant to various chemicals, water &amp; water vapour</li> <li>• Easy to apply resistant to microorganism growth</li> <li>• Economic</li> <li>• Ideal for kitchen furniture, wooden floor &amp; items exposed to water &amp; moisture</li> </ul>	<p><b>FEATURES</b></p>
<ul style="list-style-type: none"> <li>• Natural wood &amp; wood substitutes like fibre board, veneer</li> <li>• Suitable for interior use.</li> <li>• Ideal for kitchen furniture, wooden floor &amp; items exposed to water &amp; moisture.</li> </ul>	<p><b>RECOMMENDED USE</b></p>
<p>Finish : Smooth</p> <p>Colour : As per company shade card.</p> <p>NVM % : 48±2</p> <p>Gloss : Matt . Silk-matt and Glossy</p> <p>Viscosity : 80-90 sec B4/30<sup>0</sup>C</p> <p>Recommended DFT : 40 -50 microns</p> <p>Application Method : Roller, Brush and Conventional Spray</p> <p>Thinner/ Tool cleaner : Lacquer Thinner WT N</p> <p>Theoretical Coverage : 11-13 m<sup>2</sup>/ Ltr</p> <p>Practical coverage : Would depend on the surface profile, application skill &amp; method loss in the container.</p> <p>Drying time : Surface dry : 1 Hour Tack free Dry :5 Hours Full Cure : Overnight</p> <p>Recoating Time : Minimum – 5 Hours , Maximum – Infinite</p> <p>Pack Size :1 Litre, 3.5 Litre, 18 Litre</p>	<p><b>SPECIFICATION &amp; OTHER INFORMATION</b></p>

<p><b>For Wooden Surfaces</b></p> <ul style="list-style-type: none"> <li>• Ensure wood is dry, clean &amp; free from contaminants. Use Vintage Thinner for cleaning the wood surface before sanding.</li> <li>• if required Sand the surface with a coarse (P 180) followed by fine sand paper (400) along the direction of the grains.</li> <li>• Dust off the surface &amp; apply two coats of Yacht varnish with a gap of 6-8 hrs.</li> <li>• If the surface is already painted &amp; the film is strongly adhered on the substrate use Wellcoat Paint Remover before sanding &amp; application of subsequent coats.</li> <li>• A coat of Maxiwood NC filler can be used if grain filling is required.</li> </ul>	<p><b>SURFACE PREPARATION &amp; SYSTEM</b></p>
--	--

<p><b>Storage &amp; Disposal</b> : Store in cool, dry condition. &amp; dispose by controlled land fill as per requirement of statutory authority. Don't empty into drains, sewers or other water courses.</p> <p>Avoid part use from the Hardener pack &amp; never keep the lid of hardener pack open.</p> <p>Flash Point : &gt;40°C</p> <p>Shelf Life : Upto 12 months under sealed condition.</p>	<p><b>STORAGE &amp; HANDLING</b></p>
---	--------------------------------------

<ul style="list-style-type: none"> <li>• Avoid contact with the skin and eye. Wear suitable protective clothing such as Overalls, goggles, dust mask and gloves. Use a barrier cream.</li> <li>• Ensure that there is adequate ventilation in the area where the product is being applied.</li> <li>• Do not breath vapour or, spray.</li> <li>• This product is flammable-Keep away from sources of ignition. Do not smoke. Take carbon-dioxide or dry chemicals.</li> <li>• In the event of accidental splashes, flush eyes with warm water &amp; wash skin with mild soap and seek quick medical advice. Never use solvent for cleaning the affected areas.</li> <li>• Inhalation &amp; Ingestion: Remove to fresh air loosen collar. Do not induce vomiting.</li> <li>• Refer to MSDS for details.</li> </ul>	<p><b>SAFETY PRECAUTIONS &amp; FIRST AID</b></p>
---	--

<p>The product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint &amp; painting system, proper surface, surface preparation &amp; application. Wellcoat Paints warranty product quality only. Product information sheet would be subject to modification as &amp; when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	<p><b>DISCLAIMER</b></p>
---	--------------------------