



Quick Dry Primer

<p>A premium quality rapid drying primer based on special binder and anticorrosive pigments.</p>	<p>PRODUCT</p>
<ul style="list-style-type: none"> • Quick Dry • Gives good anticorrosive properties • Gives flexible, tough, abrasion & scratch resistance film. • Increases shop floor productivity and specially designed for steel structure, tanks, pipes, scaffolding painting. 	<p>FEATURES</p>
<p>Suggested for Scaffolding, Grills/ Steel structures, Slotted angle racks, other light industrial items where substrate is steel. This is a one coat product & usable in interior & exterior.</p>	<p>RECOMMENDED USE</p>
<p>Finish : Smooth</p> <p>Color : Red/ Grey</p> <p>Gloss : Matt</p> <p>% Volume Solid : 65±2</p> <p>Dry Film Thickness : 55-65 microns</p> <p>Thinner/Tool cleaner : QD Thinner</p> <p>Method of Application : Conventional Spray, Roller, Brush, Dipping</p> <p>Theoretical Coverage : Approximately 12-10 m²/lt</p> <p>Practical coverage : Would depend on the surface profile, application skill & method, loss in the container.</p> <p>Drying time @ 30°C : Surface dry 5 minutes Tack free dry 15 minutes Recoating time 30 minutes (min) & infinite (max)</p> <p>Conventional Spray : Tip size – 1.80- 2.20mm, Pressure- 40 -50 psi</p> <p>Airless Spray : Tip size – 0.38- 0.43mm, Pressure- 1600 -2300 psi</p> <p>Pack size : 18 litre,200 litre</p>	<p>SPECIFICATION & OTHER INFORMATION</p>

<ul style="list-style-type: none"> • Surface should be clean from all dust, rust, wax, oil, grease, loose particles, flakes and other contaminants. • Abrasive blast cleaning of the surface should meet minimum standard of SSPC-SP-10 OR Swedish standard Sa 2 1/2 – SIS 05 5900 or ISO 8501:1988. • Applicable by conventional spray at viscosity of 25-30 sec B4/25°C • The product can be applied by Brush over a small area. Large area is difficult due to the fast-drying nature of the paint & consequent brush drag. • Ensure adequate ventilation in the application area. Don't apply when humidity exceeds 95% & substrate temperature is within 3°C of dew point. 	SURFACE PREPARATION & APPLICATION
--	--

<p>Storage & Disposal : Store in cool, dry condition. & dispose by controlled land fill as per requirement of statutory authority. Don't empty into drains, sewers or other water courses.</p> <p>Shelf Life : Upto 12 months under sealed condition.</p>	STORAGE & HANDLING
---	-----------------------------------

<ul style="list-style-type: none"> ▪ Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. ▪ Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapor or spray. ▪ This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge. In case of fire, blanket flames with foam, carbon-dioxide or dry chemicals. ▪ Eyes & Skin: In the event of accidental splashes, flush eyes with warm water & wash skin with mild soap and seek quick medical advice. Never use solvent for cleaning the affected areas. ▪ Inhalation & Ingestion: Remove to fresh air, loosen collar. Don't induce vomiting. 	SAFETY PRECAUTIONS & FIRST AID
--	---

<p>The product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system, proper surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product.</p> <p>Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	DISCLAIMER
---	-------------------