

Supercryl Enamel

<p>A Solvent borne single pack thermoplastic acrylic resin with good water, chemical & weather resistance. The Product is based on Rutile grade titanium dioxide & high quality pigments & extenders to bolster weather & chemical resistance. The product is designed to perform as anti-carbonation coating when used as topcoat in Texo Tile hybrid system.</p>	<p>PRODUCT</p>
<ul style="list-style-type: none"> • Anti-carbonation coating. • Quicker drying. • Very hard after overnight. • High gloss & non yellowing. 	<p>FEATURES</p>
<p>Area of Use : Exterior & Interior Substrate : Concrete, plaster, masonry, gypsum, brickwork, block work, timber.</p>	<p>RECOMMENDED USE</p>
<p>Finish : Hi-Gloss / Semigloss Colour : As per Wellcoat shade card NVM % : 45 ± 2 Specific Gravity : 1.2 ± 0.02 Thinner/Cleaner : FD Thinner Theoretical Coverage : 9-11 m² / Ltr at 50 microns DFT Practical Coverage : While estimating the practical coverage, due allowance should be made for surface preparation, uneven application, losses in containers and equipment & Loss during application Drying Time : 1 Hours @ 30°C Overcoating Interval : Minimum -10 Hours , Maximum - Indefinite Pack size : 1USG,5USG</p>	<p>SPECIFICATION & OTHER INFORMATION</p>

<p>Applicable by Brush, Roller Conventional spray & Air less spray. On masonry surface application by Roller or Brush give satisfactory performance but spray application is suggested over Timber & Metal substrates. Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Minimum two coats are recommended for best performance. Use 5% to 10% thinner for ease of application depending on the method of application.</p>	APPLICATION METHOD
--	---------------------------

<p>For unpainted surface Concrete, Plaster, Masonry, Gypsum, Brickwork & Blockwork: Clean surface from all contaminants & laitance by wire brush or sweep blast followed by dry ragging. Apply a coat of Wellcoat alkali resistant primer or tex primer followed by Wellcoat Texo Compound & allow to dry over night before application of Supercryl.</p> <p>For Prepainted Surfaces (Concrete, masonry, gypsum etc) Previously painted surface should be freed of chalking or friable material by wire brushing, scrapping followed by dusting down with dry rag & allow to dry before application of Supercryl.</p> <p>Timber & Metal surface Clean the surface thoroughly using sandpaper & dust it down using clean rag. Apply directly over wooden or metal substrate two coats of Supercryl by spray with a gap of 2-3 hrs between each coat.</p>	SURFACE PREPARATION & SYSTEM
---	---

<p>Storage & Disposal : Store under cool & dry condition with adequate ventilation. Dispose in land fill as per guidance of statutory authority Do not empty the cans in drains, sewers, or other water courses.</p> <p>Flash point : 27°C</p> <p>Shelf life : 12 months in closed condition</p>	STORAGE & HANDLING
---	-------------------------------

<ul style="list-style-type: none"> • Avoid contact with the skin and eyes. Wear protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. • Ensure that there is adequate ventilation in the area where the product is being applied. • For details on Safety & Handling refer to MSDS. 	SAFETY PRECAUTIONS & FIRST AID
--	---

<p>The Product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of ,paint & painting system, proper surface, surface preparation & application. Unless specifically agreed in writing by us we will not be responsible for 100% performance of the product. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	DISCLAIMER
---	-------------------