



Light Weight Body Filler

Light weight filler is a thixotropic two component polyester putty used for filling holes and imperfections.	PRODUCT
<ul style="list-style-type: none">• Fast dry• Maximum Filling• Excellent adhesion• Easy sanding	FEATURES
Car repair, Industrial coating, Bare steel and properly prepared old finishes.	RECOMMENDED USE
<p>Finish : Smooth</p> <p>Viscosity : 400,000-500,000 cP @ 30°C</p> <p>Colour : Grey and Yellow</p> <p>Density : 1.4 ± 0.1 gram/cm³</p> <p>Mixing ratio : Base :Hardener = 100:2</p> <p>Pot Life : 3-5 miuntes</p> <p>Drying time @ 30°C : Dry Sanding 20 minutes</p> <p>Sandpaper : P80-P120 followed by P220-P320</p> <p>Pack size : 1 kg, 1.5kg, 2kg, 3.5kg, 5kg</p>	SPECIFICATION & OTHER INFORMATION

<p>Storage & Disposal : Store in cool, dry condition. & dispose by controlled land fill as per requirement of statutory authority. Don't empty into drains, sewers or other water courses. Never keep the lid of hardener pack open.</p> <p>Flash Point : 30°C</p> <p>Shelf Life : Up to 6 months under sealed condition.</p>	<p>STORAGE & HANDLING</p>
---	--------------------------------------

<ul style="list-style-type: none"> ▪ Avoid contact with the skin and eyes. Wear suitable protective clothings such as overalls, goggles, dust mask and gloves. Use a barrier cream. ▪ Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray. ▪ This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge. In case of fire, blanket flames with foam, carbon-dioxide or dry chemicals. ▪ Eyes & Skin: In the event of accidental splashes, flush eyes with warm water & wash skin with mild soap and seek quick medical advice. Never use solvent for cleaning the affected areas. ▪ Inhalation & Ingestion: Remove to fresh air, loosen collar. Don't induce vomiting. 	<p>SAFETY PRECAUTIONS & FIRST AID</p>
--	--

<p>The product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system, proper surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	<p>DISCLAIMER</p>
--	--------------------------