

<p>NC putty is a quick drying easy to apply filler for metal substrates. The product is having excellent filling &amp; sanding property for auto refinishing application .</p>	<p><b>PRODUCT</b></p>
<ul style="list-style-type: none"> <li>• Very good filling property,</li> <li>• Good Sandability</li> <li>• Can develop adequate film build giving rise to excellent finish of the system.</li> </ul>	<p><b>FEATURES</b></p>
<p>Auto Refinish, metal substrates</p>	<p><b>RECOMMENDED USE</b></p>
<p>Specific gravity : 1.43-1.45        % NVM : Appx 70%        Viscosity/ Consistency : 200,000 cPS @30°C &amp; thixotropic        Thinning : Not required        Drying &amp; Sanding time : 30 minutes at 30°C        Method of application : Putty knife, Spatula, Stopping knife        Pack size : 1LT.1 USG, 5 USG</p>	<p><b>SPECIFICATION &amp; OTHER INFORMATION</b></p>

<p>Storage &amp; Disposal Store in cool, dry condition keeping container tightly closed in accordance with petroleum (mixture) order, SRO 1929 No 993. &amp; dispose by controlled land fill as per requirement of statutory authority. Don't empty into drains, sewers or other water courses.</p> <p>Flash Point : Below 20°C, Highly flammable.</p> <p>Shelf Life : Upto 12 months in closed condition</p>	<p><b>STORAGE &amp; HANDLING</b></p>
---	--------------------------------------

<p>Ensure surface to be applied is dry, clean &amp; free from contaminants. Sand the surface with a coarse Emery (180) along the direction of grains. Dust off the surface &amp; apply a coat of N.C. Putty with putty knife, allow it to dry &amp; sand the surface with Emery paper 180 followed by Emery paper no 320 for smooth finish before application of primer &amp; Topcoat. Product's high solid formula ensures single coat application for desired result.</p>	<p><b>SURFACE PREPARATION &amp; APPLICATION</b></p>
---	---

<ul style="list-style-type: none"> <li>▪ Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream.</li> <li>▪ Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapor or spray.</li> <li>▪ This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge. In case of fire, blanket flames with foam, carbon-dioxide or dry chemicals.</li> <li>▪ Eyes &amp; Skin: In the event of accidental splashes, flush eyes with warm water &amp; wash skin with mild soap and seek quick medical advice. Never use solvent for cleaning the affected areas.</li> <li>▪ Inhalation &amp; Ingestion: Remove to fresh air, loosen collar. Don't induce vomiting.</li> </ul>	<p><b>SAFETY PRECAUTIONS &amp; FIRST AID</b></p>
--	--

<p>The product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint &amp; painting system, proper surface, surface preparation &amp; application. Wellcoat Paints warranty product quality only. Product information sheet would be subject to modification as &amp; when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	<p><b>DISCLAIMER</b></p>
---	--------------------------