

**Polyester Putty Regular**

<p>Two component unsaturated polyester putty helps in repairing wooden as well as steel surface by filling dents, pinholes and scratches.</p>	<p><b>PRODUCT</b></p>
<ul style="list-style-type: none"> <li>• Fast dry</li> <li>• Maximum Filling</li> <li>• Excellent adhesion</li> <li>• Easy sanding</li> </ul>	<p><b>FEATURES</b></p>
<p>Car repair, Industrial coating, Bare steel and properly prepared old finishes.</p>	<p><b>RECOMMENDED USE</b></p>
<p>Finish : Smooth          Viscosity : 400,000-500,000 cP @ 30°C          Colour : Grey and Yellow          Density : 1.7 ± 0.1 gram/cm<sup>3</sup>          Mixing ratio : Base :Hardener = 100:2          Pot Life : 3-5 miuntes          Drying time @ 30°C : Dry Sanding 20 minutes          Sandpaper : P80-P120 followed by P220-P320          Pack size : 1 kg, 1.5kg, 2kg, 3.5kg, 5kg</p>	<p><b>SPECIFICATION &amp; OTHER INFORMATION</b></p>

<p>Storage &amp; Disposal : Store in cool, dry condition. &amp; dispose by controlled land fill as per requirement of statutory authority. Don't empty into drains, sewers or other water courses. Never keep the lid of hardener pack open.</p> <p>Flash Point : 30°C</p> <p>Shelf Life : Up to 6 months under sealed condition.</p>	<p><b>STORAGE &amp; HANDLING</b></p>
---	--------------------------------------

<ul style="list-style-type: none"> <li>▪ Avoid contact with the skin and eyes. Wear suitable protective clothings such as overalls, goggles, dust mask and gloves. Use a barrier cream.</li> <li>▪ Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.</li> <li>▪ This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge. In case of fire, blanket flames with foam, carbon-dioxide or dry chemicals.</li> <li>▪ Eyes &amp; Skin: In the event of accidental splashes, flush eyes with warm water &amp; wash skin with mild soap and seek quick medical advice. Never use solvent for cleaning the affected areas.</li> <li>▪ Inhalation &amp; Ingestion: Remove to fresh air, loosen collar. Don't induce vomiting.</li> </ul>	<p><b>SAFETY PRECAUTIONS &amp; FIRST AID</b></p>
--	--

<p>The product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint &amp; painting system, proper surface, surface preparation &amp; application. Wellcoat Paints warranty product quality only. Product information sheet would be subject to modification as &amp; when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	<p><b>DISCLAIMER</b></p>
---	--------------------------