



2K Filler

<p>Two component acrylic filler applied before the application of 2k acrylic paints or solvent based basecoats in order to obtain maximum filling and superior finish.</p>	<p>PRODUCT</p>
<ul style="list-style-type: none">• Maximum Filling• Excellent adhesion• Easy sanding	<p>FEATURES</p>
<p>Car repair, Industrial coating, Bare steel and properly prepared old finishes.</p>	<p>RECOMMENDED USE</p>
<p>Finish : Matt Viscosity : 90 ± 5 Kerbs unit @ 30°C Colour : Grey, White & Black Density : 1.6 ± 0.1 gram/cm³ Mixing ratio : Base :Hardener = 4:1 Pot Life : 4 hrs Drying time @ 20°C : 3.5-4 hrs Sandpaper : P320 followed by P600 Pack size : 1 Litre Pressure : 2-3 bar Nozzle dia : 1.8-2mm</p>	<p>SPECIFICATION & OTHER INFORMATION</p>

<ul style="list-style-type: none"> • Surface should be clean from all dust, rust, wax, oil, grease, loose particles, flakes and other contaminants. • 2k Filler can be applied over Polyester putty, epoxy primer. • Remove dust from the surface. • Substrate temperature min: 8°C, max: 35°C • Surface to be recoat should be cleaned thoroughly before application. 	SURFACE PREPARATION & APPLICATION
---	--

<p>Storage & Disposal : Store in cool, dry condition. & dispose by controlled land fill as per requirement of statutory authority. Don't empty into drains, sewers or other water courses. Never keep the lid of hardener pack open.</p> <p>Shelf Life : Up to 1 year under sealed condition.</p>	STORAGE & HANDLING
---	-----------------------------------

<ul style="list-style-type: none"> ▪ Avoid contact with the skin and eyes. Wear suitable protective clothings such as overalls, goggles, dust mask and gloves. Use a barrier cream. ▪ Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray. ▪ This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge. In case of fire, blanket flames with foam, carbon-dioxide or dry chemicals. ▪ Eyes & Skin: In the event of accidental splashes, flush eyes with warm water & wash skin with mild soap and seek quick medical advice. Never use solvent for cleaning the affected areas. ▪ Inhalation & Ingestion: Remove to fresh air, loosen collar. Don't induce vomiting. 	SAFETY PRECAUTIONS & FIRST AID
--	---

<p>The product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system, proper surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	DISCLAIMER
--	-------------------