

Maxigloss Enamel

<p>A High gloss enamel based long oil alkyd modified with additives for imparting non-yellowing property. The product contains high percentage of Rutile titanium dioxide & other light fast pigments for improved color fastness & high opacity. Special surface additives in the formulation make the product tough and fast drying.</p>	<p>PRODUCT</p>
<ul style="list-style-type: none"> • Less yellowing • Faster drying so quicker recoating time & less dust attraction. • Improved scratch resistant. • Lead free. 	<p>FEATURES</p>
<p>Metal, Timber. Can also be used on masonry surfaces after suitable surface preparation.</p>	<p>RECOMMENDED USE</p>
<p>Finish : High gloss, Smooth & uniform Colour : As per company standard shade card , RAL, Pantone and NCS NVM % : 48±2 Specific Gravity : 1.05 ± 0.02 Application method : Brush & Roller , Conventional spray Thinner & thinning ratio : WT-N / Thinner for Enamel Theoretical coverage : 12.0 m²/lt. at 40 microns DFT Pack size : 1LT, 1USG, 5USG</p>	<p>SPECIFICATION & OTHER INFORMATION</p>

<p>For Metal Surface should be clean, dry and free from all contaminants. Remove rust, if any, by sanding or wire brushing. Wipe it clean & apply one coat of Redoxide / Red oxide Zinc phosphate primer or Wellcoat universal primer. Allow it to dry & apply two coats of Maxi gloss enamel with a gap of overnight between each coat.</p> <p>For Timber Surface should be clean, dry and free from all contaminants. Apply one coat of Wellcoat Synthetic wood primer or Wellcoat universal primer followed by two coats of Maxi gloss enamel with a gap of overnight.</p> <p>For Masonry Surface should be clean, dry and free from all contaminants. Remove laitance if any by wire brush wipe clean & apply two coats of Wellcoat universal primer. Allow it to dry for overnight & apply two coats of Maxigloss synthetic enamel.</p>	<p>SURFACE PREPARATION & APPLICATION</p>
---	---

<p>Storage & Disposal : Store in cool, dry condition. & dispose by controlled land fill as per requirement of statutory authority. Don't empty into drains, sewers or other water courses.</p> <p>Flash Point : 40°C</p> <p>Shelf Life : Upto 12 months under sealed condition.</p>	<p>STORAGE & HANDLING</p>
---	--

<ul style="list-style-type: none"> • Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, • goggles, dust mask and gloves. Use a barrier cream. • Ensure that there is adequate ventilation in the area where the product is being applied. • Do not breathe vapour or spray. • In the event of accidental splashes, flush eyes with warm water & wash skin with mild soap and seek quick medical advice. • Inhalation & Ingestion : Remove to fresh air, loosen collar. Don't induce vomiting.. • Refer to MSDS for details. 	<p>SAFETY PRECAUTIONS & FIRST AID</p>
---	--

<p>The product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system, proper surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product.</p> <p>Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	<p>DISCLAIMER</p>
---	--------------------------