

Wellcoat Paints

Painting Solution



Wellcoat Paints
Architectural Coatings
Product Data Sheet

POLYSHIELD EXTERIOR GLAZE (W.B)

A pure acrylic (water based) transparent/translucent product containing water & dust repellent additives plus UV inhibitor. On full cure the product forms a tough film designed for application over Polyshield quartz effect finish for enhanced protection & aesthetics. Polyshield glaze is available in select fast colors suiting color synergy with the base coat.

PRODUCT

Water repellent.
Available in clear & select fast colors.
Less dirt attraction.
Contains UV inhibitor.
Uniform film without patch mark.

FEATURES

- **Area of Use** : Interior & Exterior
- **Substrate** : Concrete, plaster, masonry surface coated with Polyshield products.

RECOMMENDED USE

Applicable by Brush , Roller & Conventional spray. Ensure adequate ventilation during application and drying.
Stirr thoroughly before application. Apply one uniform coat for best performance.
Use 5% to 10% thinner for ease of application depending on the method of application.
Don't apply when humidity exceeds 95%.

APPLICATION METHOD

Finish : Matt, Smooth.
Colour : Clear & select transparent colors.
NVM% : 25 ± 1
Specific Gravity : 1.08 ± 0.02
Thinner/Cleaner : Sweet Water/ WT -AQ.
Pack size : 5USG
Theoretical Coverage : 6-10 sqm. per liter depending on profile of effect coat.
Practical Coverage : Practical coverage would depend on surface profile of effect coat , loss during application & in container as well as absorption of the glaze coat onto effect coat.

SPECIFICATION & OTHER INFORMATION

■ Drying Time

Substrate temperature	Dry to touch	Overcoating interval	
		Minimum	Maximum
35°C	20 minutes	3 Hours	Indefinite

Wellcoat Paints

Painting Solution



Wellcoat Paints
Architectural Coatings
Product Data Sheet

POLYSHIELD EXTERIOR GLAZE (W.B)

Storage & Disposal : Store under cool & dry condition with adequate ventilation.
Dispose in land fill as per guidance of statutory authority
Don't empty the cans in drains, sewers or other water courses.
Flash point : Not applicable.
Shelf life : 12 months in closed condition.

STORAGE & HANDLING

- Avoid contact with the skin and eyes. Wear protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream.
- Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.
In case of accidental splashes wash the eyes with water & skin with mild soap & water. Never use solvent for cleaning body.
In case of inhalation & ingestion expose the person to fresh air & finally consult doctor as quickly as possible.
- For details on Safety & Handling refer to MSDS.

SAFETY PRECAUTIONS & FIRST AID

The Product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system , proper surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product.
Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.

DISCLAIMER